

<http://www.glaciallight.com>


7F, No.352, Sec. 2, Zhongshan Rd., Zhonghe Dist., New Taipei City, Taiwan, 235, R.O.C.

Operator
Telephone +886 2 2244-1227
Fax +886 2 2244-1241
e-Mail sales@GlacialLight.com

GlacialLight GL-DLC06-15-CW-5000K-90D / Luminaire Data Sheet

Luminous emittance 1:

See our luminaire catalog for an image of the luminaire.



Luminaire classification according to CIE: 100
CIE flux code: 70 94 98 100 101

Luminous emittance 1:

Glare Evaluation According to UGR											
ρ Ceiling	70	70	50	50	30	70	70	50	50	30	
ρ Walls	50	30	50	30	30	50	30	50	30	30	
ρ Floor	20	20	20	20	20	20	20	20	20	20	
Room Size X Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis					
2H	2H	18.8	19.8	19.0	20.0	20.2	18.8	19.8	19.1	20.0	20.2
	3H	18.8	19.7	19.1	19.9	20.2	18.8	19.7	19.1	20.0	20.2
	4H	18.7	19.6	19.0	19.8	20.1	18.8	19.7	19.1	19.9	20.2
	6H	18.7	19.5	19.0	19.7	20.0	18.8	19.6	19.2	19.9	20.2
	8H	18.7	19.4	19.0	19.7	20.0	18.8	19.6	19.2	19.9	20.2
4H	12H	18.7	19.4	19.0	19.7	20.0	18.8	19.5	19.2	19.8	20.2
	2H	18.7	19.5	19.0	19.8	20.1	18.7	19.6	19.1	19.9	20.1
	3H	18.7	19.4	19.1	19.8	20.1	18.8	19.5	19.2	19.8	20.2
	4H	18.7	19.4	19.1	19.7	20.0	18.8	19.5	19.2	19.8	20.2
	6H	18.7	19.3	19.1	19.6	20.0	18.9	19.4	19.3	19.8	20.2
8H	12H	18.7	19.2	19.1	19.6	20.0	18.9	19.4	19.3	19.8	20.2
	12H	18.7	19.2	19.2	19.6	20.0	18.9	19.3	19.4	19.8	20.2
	4H	18.7	19.2	19.1	19.5	20.0	18.8	19.3	19.2	19.7	20.1
	6H	18.7	19.1	19.1	19.5	20.0	18.8	19.2	19.3	19.7	20.1
	8H	18.7	19.1	19.2	19.5	20.0	18.9	19.2	19.4	19.7	20.1
12H	12H	18.8	19.0	19.2	19.5	20.0	18.9	19.2	19.4	19.7	20.2
	4H	18.6	19.1	19.1	19.5	19.9	18.8	19.2	19.2	19.6	20.0
	6H	18.7	19.0	19.1	19.5	19.9	18.8	19.2	19.3	19.6	20.1
8H	18.7	19.0	19.2	19.5	20.0	18.9	19.2	19.4	19.6	20.1	
Variation of the observer position for the luminaire distances S											
S = 1.0H	+1.5 / -3.1					+1.4 / -2.9					
S = 1.5H	+3.5 / -4.5					+3.4 / -4.0					
S = 2.0H	+5.4 / -6.1					+5.2 / -5.2					
Standard table	BK01					BK01					
Correction Summand	0.9					1.0					
Corrected Glare Indices referring to 1720lm Total Luminous Flux											


<http://www.glaciallight.com>

7F, No.352, Sec. 2, Zhongshan Rd., Zhonghe Dist., New Taipei City,
Taiwan, 235, R.O.C.

Operator
Telephone +886 2 2244-1227
Fax +886 2 2244-1241
e-Mail sales@GlacialLight.com

GlacialLight GL-DLC06-15-CW-5000K-90D / LDC (Polar)

Luminaire: GlacialLight GL-DLC06-15-CW-5000K-90D
Lamps: 1 x GL-DLC06-15-CW-5000K-90D



cd/klm

— C0 - C180 — C90 - C270

$\eta = 101\%$


<http://www.glaciallight.com>

7F, No.352, Sec. 2, Zhongshan Rd., Zhonghe Dist., New Taipei City,
Taiwan, 235, R.O.C.

Operator
Telephone +886 2 2244-1227
Fax +886 2 2244-1241
e-Mail sales@GlacialLight.com

GlacialLight GL-DLC06-15-CW-5000K-90D / LDC (Linear)

Luminaire: GlacialLight GL-DLC06-15-CW-5000K-90D
Lamps: 1 x GL-DLC06-15-CW-5000K-90D



http://www.glaciallight.com

7F, No.352, Sec. 2, Zhongshan Rd., Zhonghe Dist., New Taipei City,
Taiwan, 235, R.O.C.

Operator
Telephone +886 2 2244-1227
Fax +886 2 2244-1241
e-Mail sales@GlacialLight.com

GlacialLight GL-DLC06-15-CW-5000K-90D / UGR-Table

Luminaire: GlacialLight GL-DLC06-15-CW-5000K-90D
Lamps: 1 x GL-DLC06-15-CW-5000K-90D

Glare Evaluation According to UGR											
ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	18.8	19.8	19.0	20.0	20.2	18.8	19.8	19.1	20.0	20.2
	3H	18.8	19.7	19.1	19.9	20.2	18.8	19.7	19.1	20.0	20.2
	4H	18.7	19.6	19.0	19.8	20.1	18.8	19.7	19.1	19.9	20.2
	6H	18.7	19.5	19.0	19.7	20.0	18.8	19.6	19.2	19.9	20.2
	8H	18.7	19.4	19.0	19.7	20.0	18.8	19.6	19.2	19.9	20.2
	12H	18.7	19.4	19.0	19.7	20.0	18.8	19.5	19.2	19.8	20.2
4H	2H	18.7	19.5	19.0	19.8	20.1	18.7	19.6	19.1	19.9	20.1
	3H	18.7	19.4	19.1	19.8	20.1	18.8	19.5	19.2	19.8	20.2
	4H	18.7	19.4	19.1	19.7	20.0	18.8	19.5	19.2	19.8	20.2
	6H	18.7	19.3	19.1	19.6	20.0	18.9	19.4	19.3	19.8	20.2
	8H	18.7	19.2	19.1	19.6	20.0	18.9	19.4	19.3	19.8	20.2
	12H	18.7	19.2	19.2	19.6	20.0	18.9	19.3	19.4	19.8	20.2
8H	4H	18.7	19.2	19.1	19.5	20.0	18.8	19.3	19.2	19.7	20.1
	6H	18.7	19.1	19.1	19.5	20.0	18.8	19.2	19.3	19.7	20.1
	8H	18.7	19.1	19.2	19.5	20.0	18.9	19.2	19.4	19.7	20.1
	12H	18.8	19.0	19.2	19.5	20.0	18.9	19.2	19.4	19.7	20.2
12H	4H	18.6	19.1	19.1	19.5	19.9	18.8	19.2	19.2	19.6	20.0
	6H	18.7	19.0	19.1	19.5	19.9	18.8	19.2	19.3	19.6	20.1
	8H	18.7	19.0	19.2	19.5	20.0	18.9	19.2	19.4	19.6	20.1
Variation of the observer position for the luminaire distances S											
S = 1.0H		+1.5 / -3.1					+1.4 / -2.9				
S = 1.5H		+3.5 / -4.5					+3.4 / -4.0				
S = 2.0H		+5.4 / -6.1					+5.2 / -5.2				
Standard table		BK01					BK01				
Correction Summand		0.9					1.0				
Corrected Glare Indices referring to 1720lm Total Luminous Flux											

The UGR values have been calculated according to CIE Publ. 117 Spacing-to-Height-Ratio = 0.25.

http://www.glaciallight.com

7F, No.352, Sec. 2, Zhongshan Rd., Zhonghe Dist., New Taipei City,
Taiwan, 235, R.O.C.

Operator
Telephone +886 2 2244-1227
Fax +886 2 2244-1241
e-Mail sales@GlacialLight.com

GlacialLight GL-DLC06-15-CW-5000K-90D / Glare Data Sheet

Luminaire: GlacialLight GL-DLC06-15-CW-5000K-90D

Lamps: 1 x GL-DLC06-15-CW-5000K-90D

Glare Evaluation According to UGR											
ρ Ceiling	70	70	50	50	30	70	70	50	50	30	
ρ Walls	50	30	50	30	30	50	30	50	30	30	
ρ Floor	20	20	20	20	20	20	20	20	20	20	
Room Size		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
X	Y										
2H	2H	18.8	19.8	19.0	20.0	20.2	18.8	19.8	19.1	20.0	20.2
	3H	18.8	19.7	19.1	19.9	20.2	18.8	19.7	19.1	20.0	20.2
	4H	18.7	19.6	19.0	19.8	20.1	18.8	19.7	19.1	19.9	20.2
	6H	18.7	19.5	19.0	19.7	20.0	18.8	19.6	19.2	19.9	20.2
	8H	18.7	19.4	19.0	19.7	20.0	18.8	19.6	19.2	19.9	20.2
	12H	18.7	19.4	19.0	19.7	20.0	18.8	19.5	19.2	19.8	20.2
4H	2H	18.7	19.5	19.0	19.8	20.1	18.7	19.6	19.1	19.9	20.1
	3H	18.7	19.4	19.1	19.8	20.1	18.8	19.5	19.2	19.8	20.2
	4H	18.7	19.4	19.1	19.7	20.0	18.8	19.5	19.2	19.8	20.2
	6H	18.7	19.3	19.1	19.6	20.0	18.9	19.4	19.3	19.8	20.2
	8H	18.7	19.2	19.1	19.6	20.0	18.9	19.4	19.3	19.8	20.2
	12H	18.7	19.2	19.2	19.6	20.0	18.9	19.3	19.4	19.8	20.2
8H	4H	18.7	19.2	19.1	19.5	20.0	18.8	19.3	19.2	19.7	20.1
	6H	18.7	19.1	19.1	19.5	20.0	18.8	19.2	19.3	19.7	20.1
	8H	18.7	19.1	19.2	19.5	20.0	18.9	19.2	19.4	19.7	20.1
	12H	18.8	19.0	19.2	19.5	20.0	18.9	19.2	19.4	19.7	20.2
12H	4H	18.6	19.1	19.1	19.5	19.9	18.8	19.2	19.2	19.6	20.0
	6H	18.7	19.0	19.1	19.5	19.9	18.8	19.2	19.3	19.6	20.1
	8H	18.7	19.0	19.2	19.5	20.0	18.9	19.2	19.4	19.6	20.1

Variation of the observer position for the luminaire distances S		
S = 1.0H	+1.5 / -3.1	+1.4 / -2.9
S = 1.5H	+3.5 / -4.5	+3.4 / -4.0
S = 2.0H	+5.4 / -6.1	+5.2 / -5.2
Standard table	BK01	BK01
Correction Summand	0.9	1.0

Corrected Glare Indices referring to 1720lm Total Luminous Flux

The UGR values have been calculated according to CIE Publ. 117 Spacing-to-Height-Ratio = 0.25.

